

DISSOLVEX

ACID DE-SCALER AND DE-RUSTER

DESCRIPTION

DISSOLVEX is a heavy duty inhibited muriatic acid de-scaler and de-ruster containing corrosion inhibitor and intended for removal of rust, heavy scale buildup, soap and alkali deposits. **DISSOLVEX** is developed for shock treatment of lines, equipment and surfaces to remove difficult mineral deposits and soils in the food processing, dairy and general industry.

SPECIFICATIONS

pH at 1.0% soln. 1.2-1.8
Form Liquid concentrate
Foam Low (controlled)
Effect on metals and plastic Safe on stainless at low dilutions and short contact time

APPLICATION

Product use is intended for difficult and heavy deposit and scale buildup. For most de-scaling application, soak parts (steel) in a tank charged with 5% - 50% (depending on buildup) of **DISSOLVEX** in water at (120°-140° F) with agitation until parts free of build up and rust. Remove and follow with a water rinse then oil parts to prevent rusting. For acid rinse applications use (1/2) ounce and up to (64) ounces with water (depending on application and build up). Always follow with a water rinse. Must wear goggles, chemical gloves and apron when handling.

Do not soak aluminum or galvanize parts in this solution.

For best results consult your Unicore technical representative.

DO NOT MIX WITH CHLORINE OR CHLORINATED PRODUCTS. TOXIC FUMES WILL BE RELEASED!

FIRST AID

DANGER! CONTAINS MURIATIC ACID. KEEP AWAY FROM CHILDREN.
Use goggles, chemical gloves, and apron.

INTERNAL: Drink plenty of water. Obtain medical guidance immediately.

EYES: Flush with cold water for 15 minutes. Obtain medical guidance immediately.

EXTERNAL: In case of contact flush with water. Remove contaminated clothing.

PACKAGING

55 gallon drums, and 5 gallon pails